



P60 2WOE

Dimensions (approx.)

Chain width:	6 mm
Chain thickness:	2,8 mm
Single tape widths:	16 mm
Length of tape ends:	top: 21±3 mm

Features

Woven polyester tape; available also with marking points and interchangeable

Slider body out of die casted zinc, puller out of zinc

Moulded components made of POM (PolyOxyMethylene)



Quality

Lateral strength	> 392 N
Lateral strength after reciprocation	> 352 N
Operating force	< 4 N
Reciprocation test (durability)	> 500 cycles
Pull off strength of puller	> 245 N
Slider locking strength	> 49 N
Slider over bottom parts	> 90 N
Lateral strength of bottom end	> 147 N

(The quality data represent minimum performance levels)

Main uses

Sportswear

Sweatshirts

Jogging suits

Work wear

Knitwear

Jackets and coats

Ski clothes

Leather goods

Sleeping bags

Outdoor goods

Fastness

		Change	Staining
Washing 60° C	(ISO 105-C06)	4	4
Water	(ISO 105-E01)	4	4
Dry-cleaning	(ISO 105-D01)	4	3...4
Light	(ISO 105-B02)	5	
Rubbing wet	(ISO 105-X12)		3... 4
Rubbing dry	(ISO 105-X12)		4

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

Standards

EN 16732 – class C	CPSIA HR4040;
BS 3084:2006;	F963;
DIN 3416 – 19;	EN71;
Oeko-Tex 100 Class 1;	QM System according BS EN ISO 9001:2008